

View Online at <https://aerobasegroup.com/nsn/4720-00-530-9365>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.391 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response

**Outside Diameter:**

0.585 inches

**Minimum Inside Bending Radius:**

4.600 inches

**Exterior Color:**

Natural

**Angle Between Rigid Elbow Fittings In Deg:**

0.0

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Elbow 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Reusable end fittings

**Thready Qty Per Inch (tpi):**

16 1st end

**Burst Test Pressure:**

8000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1500.0 pounds per square inch

**Thread Size:**

0.750 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

3000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 1st end

**Outer Covering Environmental Protection:**

Corrosion resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

35.500 inches working

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response and fuel/oil, hydrocarbon single response and hydraulic fluid single response and hydraulic fluid, phosphate-ester base single response

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0