

View Online at <https://aerobasegroup.com/nsn/4720-00-532-5380>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.313 inches and 0.344 inches

Outside Diameter:

Between 0.656 inches and 0.670 inches

Minimum Inside Bending Radius:

4.000 inches

Angle Between Rigid Elbow Fittings In Deg:

45.0

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

18 1st end

Burst Test Pressure:

9000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided wire and 1st layer braided cotton cord and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

2000.0 pounds per square inch

Thread Size:

0.562 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

4500.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Outer Covering Environmental Protection:

Fuel resistant and oil resistant

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

34.750 inches working and 35.250 inches working

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Unj 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0