NSN 4720-00-533-3396

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-533-3396

·					
Cross Sectional Shape:					
Round					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
2.000 inches					
Tempurature Rating:					
-67.0 degrees fahrenheit and 250.0 degrees fahrenheit single response					
Outside Diameter:					
2.625 inches					
Minimum Inside Bending Radius:					
22.000 inches					
Connection Style:					
Inverted flare 1st end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded external pipe 1st end					
Burst Test Pressure:					
1500.0 pounds per square inch					
Layer Composition And Location:					
Outer layer molded rubber, chloroprene and 1st layer braided steel wire					
Maximum Operating Pressure:					
375.0 pounds per square inch					
Thread Size:					
2.000 inches 1st end					
Seat Angle:					
30.0 degrees 1st end					
Hydrostatic Test Pressure:					
750.0 pounds per square inch					
Outer Covering Environmental Protection:					
Mildew resistant and oil resistant and oil resistant					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
34.000 inches					
Media For Which Designed:					
Fuel/oil, hydrocarbon single response					
Thread Series Designator:					
Nptf 1st end					
Shelf Life:					
N/a					

N/a

NSN 4720-00-533-3396

Nonmetallic Hose Assembly - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-dtl-13531 spec.