

View Online at <https://aerobasegroup.com/nsn/4720-00-533-6872>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.375 inches

Temperature Rating:

-65.0 degrees fahrenheit and 375.0 degrees fahrenheit single response

Flange Thickness:

0.355 inches 2nd end

Outside Diameter:

1.704 inches

Minimum Inside Bending Radius:

9.000 inches

Exterior Color:

Natural

Angle Between Rigid Elbow Fittings In Deg:

270.0

Center To Center Distance Between Bolt Holes Along Width:

1.812 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

1.812 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

2.385 inches 2nd end

Flange Width:

2.385 inches 2nd end

Connection Style:

Swivel nut flare 1st end

Bolt Hole Diameter:

0.270 inches 2nd end

Raised Face Height:

0.015 inches 2nd end

Raised Face Diameter:

2.125 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

2000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverage

Maximum Operating Pressure:

250.0 pounds per square inch

Thread Size:

1.875 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

800.0 pounds per square inch

Flow Angle:

60.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

17.500 inches working

Flange Style:

Rectangular (includes square) 2nd end

Special Features:

Elbow on first end has internal boss fitting welded into nipple, 0.625 in.-18, unf thd @size

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0