Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-539-8862
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.312 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.590 inches
Minimum Inside Bending Radius:
4.500 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Perforated outer cover
Burst Test Pressure:
10000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided synthetic cord and 1st layer braided synthetic cord and outer layer molded plastic
Maximum Operating Pressure:
2500.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
45.0 degrees 1st end
Hydrostatic Test Pressure:
5000.0 pounds per square inch
Outer Covering Environmental Protection:
Hydraulic solution resistant and oil resistant and ozone resistant and weatherproof
Inside Surface Condition:
Smooth
Management Matthe ad Angel Langetha

Measuring Method And Length:

57.500 inches

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0