Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-539-8925

| view Online at https://aerobasegroup.com/hsi//4/20-00-559-6925 | |
|--|----|
| Cross Sectional Shape: | |
| Round | |
| Thread Class: | |
| 2b 1st end | |
| Thread Direction: | |
| Right-hand 1st end | |
| Inside Diameter: | |
| 1.250 inches | |
| Tempurature Rating: | |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response | se |
| Outside Diameter: | |
| 2.250 inches | |
| Minimum Inside Bending Radius: | |
| 5.000 inches | |
| Exterior Color: | |
| Black | |
| Connection Style: | |
| Swivel nut flare 2nd end | |
| End Connection Design: | |
| Straight 1st end | |
| Connection Type: | |
| Threaded internal tube 1st end | |
| Features Provided: | |
| Reusable end fittings | |
| Thready Qty Per Inch (tpi): | |
| 12 2nd end | |
| Burst Test Pressure: | |
| 200.0 pounds per square inch | |
| Layer Composition And Location: | |
| Outer layer spirally wrapped rubber fabric and 1st layer braided fiber | |
| Maximum Operating Pressure: | |
| 50.0 pounds per square inch | |
| Thread Size: | |
| 1.625 inches 2nd end | |
| Seat Angle: | |
| 37.0 degrees 2nd end | |
| Hydrostatic Test Pressure: | |
| 100.0 pounds per square inch | |
| Flow Angle: | |
| 45.0 degrees 2nd end | |
| Inside Surface Condition: | |
| Smooth | |



Measuring Method And Length:

29.000 inches working

Media For Which Designed:

Water single response

Thread Series Designator:

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0