

View Online at <https://aerobasegroup.com/nsn/4720-00-540-1331>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

1.125 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

1.500 inches

**Minimum Inside Bending Radius:**

9.000 inches

**Connection Style:**

Plain 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded external pipe 1st end

**Features Provided:**

Reusable end fittings

**Burst Test Pressure:**

2500.0 pounds per square inch

**Layer Composition And Location:**

2nd layer braided cotton cord and 1st layer braided wire and outer layer rubber impregnated braided cotton cord

**Maximum Operating Pressure:**

625.0 pounds per square inch

**Thread Size:**

1.250 inches 1st end

**Hydrostatic Test Pressure:**

1250.0 pounds per square inch

**Outer Covering Environmental Protection:**

Fuel resistant and mildew resistant and oil resistant and waterproof

**Vacuum In Torr:**

508.0

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

18.375 inches

**Media For Which Designed:**

Fuel/oil, hydrocarbon and water, fresh single response

**Thread Series Designator:**

Npt 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0