Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-540-1331

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.125 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.500 inches
Minimum Inside Bending Radius:
9.000 inches
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
2500.0 pounds per square inch
Layer Composition And Location:
2nd layer braided cotton cord and 1st layer braided wire and outer layer rubber impregnated braided cotton cord
Maximum Operating Pressure:
625.0 pounds per square inch
Thread Size:
1.250 inches 1st end
Hydrostatic Test Pressure:
1250.0 pounds per square inch
Outer Covering Environmental Protection:
Fuel resistant and mildew resistant and oil resistant and waterproof
Vacuum In Torr:
508.0
Inside Surface Condition:
Smooth
Measuring Method And Length:
18.375 inches
Media For Which Designed:
Fuel/oil, hydrocarbon and water, fresh single response
Thread Series Designator:
Npt 1st end

NSN 4720-00-540-1331

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

