

View Online at <https://aerobasegroup.com/nsn/4720-00-540-1332>

Cross Sectional Shape:

Round

Inside Diameter:

1.812 inches

Temperature Rating:

-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Flange Thickness:

0.359 inches 1st end

Outside Diameter:

2.000 inches

Minimum Inside Bending Radius:

13.100 inches

Center To Center Distance Between Bolt Holes Along Width:

2.375 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

2.375 inches 1st end

Bolt Hole Quantity:

4 2nd end

Flange Length:

3.000 inches 1st end

Flange Width:

3.000 inches 1st end

Connection Style:

Raised swivel 1st end

Bolt Hole Diameter:

0.328 inches 1st end

Raised Face Height:

0.020 inches 1st end

Raised Face Diameter:

2.750 inches 1st end

End Flange Construction:

Split 1st end

End Connection Design:

Straight 1st end

Connection Type:

Raised face flange 1st end

Burst Test Pressure:

1400.0 pounds per square inch

Layer Composition And Location:

2nd layer braided steel wire and 1st layer rubber impregnated fabric and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

350.0 pounds per square inch

Hydrostatic Test Pressure:

700.0 pounds per square inch

Outer Covering Environmental Protection:

Mildew resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

32.000 inches working

Flange Style:

Rectangular (includes square) 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0