

View Online at <https://aerobasegroup.com/nsn/4720-00-540-1332>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

1.812 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Flange Thickness:**

0.359 inches 1st end

**Outside Diameter:**

2.000 inches

**Minimum Inside Bending Radius:**

13.100 inches

**Center To Center Distance Between Bolt Holes Along Width:**

2.375 inches 1st end

**Center To Center Distance Between Bolt Holes Along Length:**

2.375 inches 1st end

**Bolt Hole Quantity:**

4 2nd end

**Flange Length:**

3.000 inches 1st end

**Flange Width:**

3.000 inches 1st end

**Connection Style:**

Raised swivel 1st end

**Bolt Hole Diameter:**

0.328 inches 1st end

**Raised Face Height:**

0.020 inches 1st end

**Raised Face Diameter:**

2.750 inches 1st end

**End Flange Construction:**

Split 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Raised face flange 1st end

**Burst Test Pressure:**

1400.0 pounds per square inch

**Layer Composition And Location:**

2nd layer braided steel wire and 1st layer rubber impregnated fabric and outer layer rubber impregnated braided cotton cord

**Maximum Operating Pressure:**

350.0 pounds per square inch

**Hydrostatic Test Pressure:**

700.0 pounds per square inch

**Outer Covering Environmental Protection:**

Mildew resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

32.000 inches working

**Flange Style:**

Rectangular (includes square) 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0