## NSN 4720-00-540-6415

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-540-6415

o a	
Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.375 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
Outside Diameter:	
0.781 inches	
Minimum Inside Bending Radius:	
5.000 inches	
Connection Style:	
Inverted flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded external pipe 1st end	
Burst Test Pressure:	
9000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer molded rubber, synthetic and 1st layer braided steel wire	
Maximum Operating Pressure:	
2250.0 pounds per square inch	
Thread Size:	
0.375 inches 1st end	
Seat Angle:	
30.0 degrees 1st end	
Hydrostatic Test Pressure:	
4500.0 pounds per square inch	
Outer Covering Environmental Protection:	
Abrasion resistant and weatherproof	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
37.000 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Nptf 1st end	
Shelf Life:	
• • •	

N/a

## NSN 4720-00-540-6415

Nonmetallic Hose Assembly - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0