NSN 4720-00-540-6416

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-540-6416 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.625 inches **Minimum Inside Bending Radius:** 4.000 inches **Connection Style:** Inverted flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external pipe 1st end **Burst Test Pressure:** 11000.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber, synthetic and 1st layer braided steel wire **Maximum Operating Pressure:** 2750.0 pounds per square inch **Thread Size:** 0.250 inches 1st end Seat Angle: 30.0 degrees 1st end **Hydrostatic Test Pressure:** 5500.0 pounds per square inch **Outer Covering Environmental Protection:** Abrasion resistant and weatherproof **Inside Surface Condition:** Smooth **Measuring Method And Length:** 28.500 inches Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Nptf 1st end

Shelf Life:

N/a

NSN 4720-00-540-6416

Nonmetallic Hose Assembly - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A542a0