

View Online at <https://aerobasegroup.com/nsn/4720-00-541-0615>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-450.0 degrees fahrenheit and 1200.0 degrees fahrenheit single response

**Outside Diameter:**

0.450 inches

**Minimum Inside Bending Radius:**

2.500 inches

**Inner Conveying Tube Style:**

Annular open-pitch corrugated

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Identical ends

**Burst Test Pressure:**

9800.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1625.0 pounds per square inch

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

3250.0 pounds per square inch

**Outer Covering Environmental Protection:**

Corrosion resistant and incombustible

**Measuring Method And Length:**

10.250 inches

**Special Features:**

Furnished w/two dust and moisture seal protective plugs

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0