NSN 4720-00-541-4979

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-541-4979

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.875 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Bolt Circle Diameter:
2.342 inches 2nd end
Flange Thickness:
0.297 inches 2nd end
Outside Diameter:
1.156 inches
Minimum Inside Bending Radius:
5.500 inches
Exterior Color:
Natural
Bolt Hole Quantity:
4 2nd end
Flange Outside Diameter:
2.875 inches 2nd end
Connection Style:
Swivel nut flare 1st end
Bolt Hole Diameter:
0.266 inches 2nd end
Raised Face Height:
0.063 inches 2nd end
Raised Face Diameter:
1.656 inches 2nd end
End Flange Construction:
Solid 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability and reusable end fittings
Thready Oty Per Inch (tpi):

12 1st end

NSN 4720-00-541-4979

Nonmetallic Hose Assembly - Page 2 of 2



Burst Test Pressure:
2500.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverage
Maximum Operating Pressure:
750.0 pounds per square inch
Thread Size:
1.312 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
1500.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Abrasion resistant and corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
27.500 inches working
Flange Style:
Round w/ bolt holes 2nd end
Media For Which Designed:
Fuel/oil, hydrocarbon and fuel/oil, hydrocarbon single response
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0