Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-541-5710

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.344 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and	160.0 degrees fahrenheit single response
Outside Diameter:	
0.766 inches	
Minimum Inside Bending Rad	lius:
5.000 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
14000.0 pounds per square inc	h
Layer Composition And Loca	ition:
2nd layer braided corrosion res	istant steel wire and 1st layer braided corrosion resistant steel wire and outer layer molded rubber,
chloroprene	
Maximum Operating Pressur	e:
3000.0 pounds per square inch	
Thread Size:	
0.562 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
7000.0 pounds per square inch	
Inside Surface Condition:	
Smooth	
Measuring Method And Leng	th:
48.000 inches working	
Media For Which Designed:	
Air and fuel/oil, hydrocarbon s	ingle response
Thread Series Designator:	
Unjf 1st end	
Specification Data:	
96906-ms28759 government s	andard

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

