## NSN 4720-00-541-7139

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-541-7139

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.000 inches
Tempurature Rating:
40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.562 inches
Minimum Inside Bending Radius:
12.000 inches
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and 2nd layer braided steel wire and 3rd layer braided steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
2000.0 pounds per square inch
Thread Size:
1.000 inches 1st end
Hydrostatic Test Pressure:
4000.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and hydraulic solution resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
24.000 inches
Media For Which Designed:
Hydraulic fluid single response
Thread Series Designator:
Nptf 1st end
Shelf Life:
N/a
Unit Of Massure:

--

## NSN 4720-00-541-7139

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0