

View Online at <https://aerobasegroup.com/nsn/4720-00-541-7189>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.750 inches

**Temperature Rating:**

-40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response

**Outside Diameter:**

1.230 inches

**Minimum Inside Bending Radius:**

9.500 inches

**Features Provided:**

Nonskive

**Burst Test Pressure:**

12000.0 pounds per square inch single response

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Hydrostatic Test Pressure:**

6000.0 pounds per square inch single response

**Outer Covering Environmental Protection:**

Abrasion resistant and mildew resistant and oil resistant

**Inside Surface Condition:**

Smooth

**Material:**

Rubber synthetic tube

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response and water, salt single response

**Supplementary Features:**

This item has been reviewed for asbestos material; the current approved sources; 01276, 006124 and 98441 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

**Specification Data:**

81349-mil-h-24135 government specification

**Specification Or Standard:**

2 class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A541z0

**Mil-std (military Standard):**

Mil-h-24135 spec.