

View Online at <https://aerobasegroup.com/nsn/4720-00-541-8613>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-40.0 degrees fahrenheit and 225.0 degrees fahrenheit single response

Outside Diameter:

0.375 inches

Minimum Inside Bending Radius:

2.000 inches

Exterior Color:

Natural

Connection Style:

Swivel, plain 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded external pipe 2nd end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

1200.0 pounds per square inch

Maximum Operating Pressure:

300.0 pounds per square inch

Thread Size:

0.125 inches 2nd end

Seat Angle:

30.0 degrees 1st end

Hydrostatic Test Pressure:

600.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and oil resistant and ozone resistant and water resistant and weatherproof

Vacuum In Torr:

254.0

Inside Surface Condition:

Smooth

Measuring Method And Length:

40.000 inches

Special Features:

Layer composition and location 1st layer molded rubber, synthetic outer cover, braided cotton cord interwoven with two spiral wires

Media For Which Designed:

Air and fuel/oil, hydrocarbon and water, fresh single response

Thread Series Designator:

Nptf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0