

View Online at <https://aerobasegroup.com/nsn/4720-00-541-9253>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b all ends

**Thread Direction:**

Right-hand all ends

**Inside Diameter:**

0.500 inches

**Outside Diameter:**

0.922 inches

**Minimum Inside Bending Radius:**

5.500 inches

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube all ends

**Burst Test Pressure:**

7000.0 pounds per square inch

**Layer Composition And Location:**

1st layer molded rubber, synthetic

**Maximum Operating Pressure:**

1750.0 pounds per square inch

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

3500.0 pounds per square inch

**Outer Covering Environmental Protection:**

Corrosion resistant and oil resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

24.000 inches working

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Specification Data:**

96906-ms28741 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0