

View Online at <https://aerobasegroup.com/nsn/4720-00-541-9268>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.500 inches

**Outside Diameter:**

0.922 inches

**Minimum Inside Bending Radius:**

5.500 inches

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

7000.0 pounds per square inch

**Layer Composition And Location:**

2nd layer braided corrosion resistant steel wire and 1st layer braided cotton cord and outer layer rubber impregnated braided cotton cord

**Maximum Operating Pressure:**

1750.0 pounds per square inch

**Thread Size:**

0.875 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

3500.0 pounds per square inch

**Outer Covering Environmental Protection:**

Mildew resistant and oil resistant

**Vacuum In Torr:**

50.8

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

38.000 inches working

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Unf 1st end

**Specification Data:**

96906-ms18036 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0