Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-541-9276

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.375 inches	
Outside Diameter:	
0.625 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Reusable end fittings	
Thready Qty Per Inch (tpi):	
18 1st end	
Burst Test Pressure:	
1000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer molded rubber, synthetic and 1st layer braided cotton cord	
Maximum Operating Pressure:	
150.0 pounds per square inch	
Thread Size:	
0.562 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
300.0 pounds per square inch	
Outer Covering Environmental Protection:	
Abrasion resistant and light resistant and oil resistant and ozone resistant	
Vacuum In Torr:	
254.0	
Inside Surface Condition:	
Smooth	
Thread Series Designator:	
Unjf 1st end	
Specification Data:	
88044-an6270 government standard	

## NSN 4720-00-541-9276

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

