Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-542-4138

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.562 inches	
Outside Diameter:	
1.031 inches	
Exterior Color:	
Natural	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Electrostatic discharge capability	
Thready Qty Per Inch (tpi):	
14 1st end	
Second End Relationship With First End:	
Identical	
Burst Test Pressure:	
12000.0 pounds per square inch	
Layer Composition And Location:	
1st layer rubber impregnated fabric	
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
0.875 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
6000.0 pounds per square inch	
Outer Covering Environmental Protection:	
Abrasion resistant	
Inside Surface Condition:	
Smooth	
Special Features:	
Inner conveying tube material-rubber, synthetic	

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:

Air and hydraulic fluid single response

## Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A542a0