## NSN 4720-00-546-4828

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

**Thread Direction:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-546-4828

Right-hand 1st end			
Inside Diameter:			
0.125 inches			
Tempurature Rating:			
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response			
Outside Diameter:			
0.250 inches			
Minimum Inside Bending Radius:			
2.000 inches			
Connection Style:			
Swivel nut flare 1st end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Features Provided:			
Electrostatic discharge capability			
Burst Test Pressure:			
12000.0 pounds per square inch			
Layer Composition And Location:			
Outer layer braided corrosion resistant steel wire			
Maximum Operating Pressure:			
1500.0 pounds per square inch			
Thread Size:			
0.375 inches 1st end			
Seat Angle:			
37.0 degrees 1st end			
Hydrostatic Test Pressure:			
3000.0 pounds per square inch			
Outer Covering Environmental Protection:			
Corrosion resistant			
Vacuum In Torr:			
50.8			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
8.000 inches			

## NSN 4720-00-546-4828

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:
	0000	_00.9.	

Unjf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0