NSN 4720-00-552-4873

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-552-4873

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.250 inches
Minimum Inside Bending Radius:
9.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided steel wire and 1st layer braided steel wire and 3rd layer molded rubber
Maximum Operating Pressure:
2250.0 pounds per square inch
Thread Size:
1.063 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
4500.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
112.000 inches working
Media For Which Designed:
Hydraulic fluid single response

NSN 4720-00-552-4873

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0