

View Online at <https://aerobasegroup.com/nsn/4720-00-554-7983>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.212 inches and 0.244 inches

Temperature Rating:

-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response

Outside Diameter:

Between 0.594 inches and 0.656 inches

Minimum Inside Bending Radius:

5.750 inches

Hose Or Tubing Specification/std Data:

Mil mil-h-8788 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

First End Fitting Specification/std Data:

Ms28760 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Nut steel 2nd end

Fitting Component And Surface Treatment:

Nut cadmium and nut zinc 2nd end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Second End Relationship With First End:

Identical

Burst Test Pressure:

16000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

2nd layer braided steel wire

Maximum Operating Pressure:

3000.0 pounds per square inch

Unable To Decode:

Unable to decode or unable to decode

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

8000.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and mildew resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

27.000 inches working

Special Features:

Inner conveying tube material-rubber, chloroprene

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0