NSN 4720-00-554-8086

Nonmetallic Hose - Page 1 of 2

Cross Sectional Shape:



View Online at https://aerobasegroup.com/nsn/4720-00-554-8086

| Round |
|---|
| Inside Diameter: |
| 0.438 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.859 inches |
| Minimum Inside Bending Radius: |
| 5.750 inches |
| Exterior Color: |
| Black |
| End Application: |
| Grumman a10 aircraft |
| Features Provided: |
| Electrostatic discharge capability |
| Burst Test Pressure: |
| 14000.0 pounds per square inch single response |
| Layer Composition And Location: |
| 1st layer braided steel wire err-100 |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch single response |
| Hydrostatic Test Pressure: |
| 7000.0 pounds per square inch single response |
| Outer Covering Environmental Protection: |
| Abrasion resistant and oil resistant |
| Inside Surface Condition: |
| Smooth |
| Material: |
| Rubber butadiene-acrylonitrile class nbr tube |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Specification Data: |
| 81349-mil-h-8788 government specification |
| Specification Or Standard: |
| 8 size |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| N- |

No

NSN 4720-00-554-8086

Nonmetallic Hose - Page 2 of 2



Fiig:

A541z0

Mil-std (military Standard):

Mil-h-8788 spec.