NSN 4720-00-554-8089

Nonmetallic Hose - Page 1 of 2

A541z0



View Online at https://aerobasegroup.com/nsn/4720-00-554-8089

Cross Sectional Shape:
Round
Inside Diameter:
Between 0.865 inches and 0.906 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response
Outside Diameter:
Between 1.469 inches and 1.547 inches
Minimum Inside Bending Radius:
9.625 inches
End Application:
Grumman a-10 aircraft
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
10000.0 pounds per square inch single response
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and 3rd layer braided corrosion resistant
steel wire and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Hydrostatic Test Pressure:
5000.0 pounds per square inch single response
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant
Inside Surface Condition:
Smooth
Material:
Rubber synthetic tube
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Specification Data:
813498788-16-b government specification
Specification Or Standard:
16 size
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

NSN 4720-00-554-8089

Nonmetallic Hose - Page 2 of 2



Mil-std (military Standard):

Mil-h-8788 spec.