

View Online at <https://aerobasegroup.com/nsn/4720-00-554-8089>

Cross Sectional Shape:

Round

Inside Diameter:

Between 0.865 inches and 0.906 inches

Tempurature Rating:

-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response

Outside Diameter:

Between 1.469 inches and 1.547 inches

Minimum Inside Bending Radius:

9.625 inches

End Application:

Grumman a-10 aircraft

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

10000.0 pounds per square inch single response

Layer Composition And Location:

1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and 3rd layer braided corrosion resistant steel wire and outer layer molded rubber, chloroprene

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Hydrostatic Test Pressure:

5000.0 pounds per square inch single response

Outer Covering Environmental Protection:

Abrasion resistant and oil resistant

Inside Surface Condition:

Smooth

Material:

Rubber synthetic tube

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Specification Data:

81349--8788-16-b government specification

Specification Or Standard:

16 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A541z0

Mil-std (military Standard):

Mil-h-8788 spec.