

View Online at <https://aerobasegroup.com/nsn/4720-00-554-8089>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

Between 0.865 inches and 0.906 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response

**Outside Diameter:**

Between 1.469 inches and 1.547 inches

**Minimum Inside Bending Radius:**

9.625 inches

**End Application:**

Grumman a-10 aircraft

**Features Provided:**

Electrostatic discharge capability

**Burst Test Pressure:**

10000.0 pounds per square inch single response

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and 3rd layer braided corrosion resistant steel wire and outer layer molded rubber, chloroprene

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Hydrostatic Test Pressure:**

5000.0 pounds per square inch single response

**Outer Covering Environmental Protection:**

Abrasion resistant and oil resistant

**Inside Surface Condition:**

Smooth

**Material:**

Rubber synthetic tube

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Specification Data:**

81349--8788-16-b government specification

**Specification Or Standard:**

16 size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A541z0

**Mil-std (military Standard):**

Mil-h-8788 spec.