

View Online at <https://aerobasegroup.com/nsn/4720-00-554-9363>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

1.500 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response

**Outside Diameter:**

2.125 inches

**Hose Or Tubing Specification/std Data:**

Mil-4-6615 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**First End Fitting Specification/std Data:**

Mil mil-c-38404, class 1, type 1, size 1-1/2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Second End Fitting Specification/std Data:**

Mil mil-c-38404, class 1, type 2, size 1-1/2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Connection Style:**

Swivel nut, gasket seal 2nd end

**End Connection Design:**

Straight 2nd end

**End Fitting Component And Material:**

Nipple copper alloy all ends

**Connection Type:**

Threaded internal hose 2nd end

**Features Provided:**

Electrostatic discharge capability

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

800.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer molded rubber, chloroprene

**Thread Size:**

1.500 inches 2nd end

**Hydrostatic Test Pressure:**

300.0 pounds per square inch

**Outer Covering Environmental Protection:**

**Measuring Method And Length:**

420.000 inches

**Second End Swivel Action Capability:**

Included

**Special Features:**

Inner conveying tube material-rubber, synthetic; spirally wound electrical bonding wires included in the reinforcement of hose

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Npt 1st end

**Specification Data:**

96906-mil-h-6615 government standard

**Specification Or Standard:**

1-1/2 size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0

**Mil-std (military Standard):**

Mil-4-6615 spec.