

View Online at <https://aerobasegroup.com/nsn/4720-00-555-0163>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.500 inches

Temperature Rating:

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Outside Diameter:

0.920 inches

Minimum Inside Bending Radius:

5.500 inches

Exterior Color:

Black

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability and reusable end fittings

Burst Test Pressure:

7000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided steel wire and 1st layer braided textile yarn and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

1750.0 pounds per square inch

Thread Size:

0.875 inches 1st end

Seat Angle:

45.0 degrees 1st end

Hydrostatic Test Pressure:

3500.0 pounds per square inch

Outer Covering Environmental Protection:

Fire retardant and oil resistant and water resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

18.250 inches

Media For Which Designed:

Alcohol, methyl and ethylene glycol and fuel/oil, hydrocarbon and water, fresh single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0