## NSN 4720-00-555-1551

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-555-1551

view Online at https://aerobasegroup.com/hish/4/20-00-000-1001
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.343 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.765 inches
Minimum Inside Bending Radius:
5.000 inches
Hose Or Tubing Specification/std Data:
Mil, mil-h-8788-6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
First End Fitting Specification/std Data:
Ms28761-6 standard (includes industry or association standards, individual manufactureer standards, etc.).
Connection Style:
Swivel nut with loose or integral clinch sleeve 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Nut steel 1st end
Fitting Component And Surface Treatment:
Nut cadmium 1st end
Connection Type:
Threaded internal tube 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
14000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
2nd layer braided steel wire
Unable To Decode:
Unable to decode or unable to decode
Maximum Operating Pressure:

Unable to decode or unable to decode

3000.0 pounds per square inch

**Unable To Decode:** 

## NSN 4720-00-555-1551

Nonmetallic Hose Assembly - Page 2 of 2



Thread Size:
0.562 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
7000.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
20.000 inches working
Special Features:
Inner conveying tube material-rubber, synthetic
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unjf 1st end
Specification Data:
96906-ms28762 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0