Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-555-1856

С	ross Sectional Shape:
R	ound
Т	hread Class:
2	b 1st end
Т	hread Direction:
R	ight-hand 1st end
In	side Diameter:
0.	250 inches
T	empurature Rating:
-4	0.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
0	utside Diameter:
0.	690 inches
Μ	linimum Inside Bending Radius:
4.	000 inches
Е	xterior Color:
В	lack
С	onnection Style:
S	wivel nut flare 1st end
Е	nd Connection Design:
S	traight 1st end
С	onnection Type:
Т	hreaded internal tube 1st end
F	eatures Provided:
R	eusable end fittings
T	hready Qty Per Inch (tpi):
2	0 1st end
в	urst Test Pressure:
2	0000.0 pounds per square inch
L	ayer Composition And Location:
1:	st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic
Μ	aximum Operating Pressure:
5	000.0 pounds per square inch
Т	hread Size:
0.	438 inches 1st end
s	eat Angle:
3	7.0 degrees 1st end
н	ydrostatic Test Pressure:
1(	0000.0 pounds per square inch
0	uter Covering Environmental Protection:
0	il resistant
In	side Surface Condition:
S	mooth

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 132.750 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: --Demilitarization: No

Fiig:

A542a0