

View Online at <https://aerobasegroup.com/nsn/4720-00-555-2894>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.625 inches

Minimum Inside Bending Radius:

4.000 inches

Exterior Color:

Black

Connection Style:

Inverted flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external pipe 1st end

Burst Test Pressure:

20000.0 pounds per square inch

Layer Composition And Location:

Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire

Maximum Operating Pressure:

5000.0 pounds per square inch

Thread Size:

0.250 inches 1st end

Seat Angle:

30.0 degrees 1st end

Hydrostatic Test Pressure:

10000.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and oil resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

18.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Nptf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0