NSN 4720-00-555-3145

Nptf 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-555-3145

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.344 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 158.0 degrees fahrenheit single response
Outside Diameter:
0.766 inches
Minimum Inside Bending Radius:
5.000 inches
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.375 inches 1st end
Seat Angle:
30.0 degrees 1st end
Hydrostatic Test Pressure:
7000.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
360.000 inches
Special Features:
Reuseable fittings
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:

NSN 4720-00-555-3145

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0