## NSN 4720-00-555-3827

**Cross Sectional Shape:** 

120.0 pounds per square inch

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-555-3827

| Cross Sectional Shape.   |
|--|
| Round  |
| Inside Diameter:   |
| 1.812 inches   |
| Tempurature Rating:  |
| -65.0 degrees fahrenheit single response                                   |
| Flange Thickness:  |
| 0.300 inches 1st end   |
| Outside Diameter:  |
| 2.094 inches   |
| Minimum Inside Bending Radius:   |
| 17.000 inches  |
| Center To Center Distance Between Bolt Holes Along Width:                  |
| 2.380 inches 1st end   |
| Center To Center Distance Between Bolt Holes Along Length:                 |
| 2.380 inches 1st end   |
| Bolt Hole Quantity:  |
| 4 1st end  |
| Flange Length:   |
| 3.000 inches 1st end   |
| Flange Width:  |
| 3.000 inches 1st end   |
| Connection Style:  |
| Raised swivel 1st end  |
| Bolt Hole Diameter:  |
| 0.270 inches 1st end   |
| Raised Face Height:  |
| 0.015 inches 1st end   |
| Raised Face Diameter:  |
| 2.750 inches 1st end   |
| End Flange Construction:   |
| Solid 1st end  |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Raised face flange 1st end   |
| Burst Test Pressure:   |
| 640.0 pounds per square inch   |
| Layer Composition And Location:  |
| 1st layer braided fabric and outer layer rubber impregnated braided fabric |
| Maximum Operating Pressure:  |
|  |

## NSN 4720-00-555-3827

Nonmetallic Hose Assembly - Page 2 of 2



## **Hydrostatic Test Pressure:** 240.0 pounds per square inch **Outer Covering Environmental Protection:** Fuel resistant and oil resistant and waterproof **Inside Surface Condition:** Smooth **Measuring Method And Length:** 24.130 inches Flange Style: Rectangular (includes square) 1st end **Special Features:** Identification band and protective closures furnished Media For Which Designed: Fuel/oil, hydrocarbon single response Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A542a0