

View Online at <https://aerobasegroup.com/nsn/4720-00-555-7938>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Connection Style:

Plain optional end 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal pipe 1st end

Features Provided:

Electrostatic discharge capability

Thready Qty Per Inch (tpi):

27 2nd end

Burst Test Pressure:

2000.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and outer layer rubber impregnated braided rayon cord

Maximum Operating Pressure:

500.0 pounds per square inch

Thread Size:

0.125 inches 2nd end

Hydrostatic Test Pressure:

1000.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and fuel resistant and mildew resistant and oil resistant and ozone resistant

Vacuum In Torr:

254.0

Inside Surface Condition:

Smooth

Media For Which Designed:

Fuel/oil, hydrocarbon and fuel/oil, hydrocarbon single response

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A542a0