

View Online at <https://aerobasegroup.com/nsn/4720-00-557-8363>

Cross Sectional Shape:

Round

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.310 inches

Temperature Rating:

-15.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

0.610 inches

Minimum Inside Bending Radius:

2.000 inches

Exterior Color:

Black

Connection Style:

Swivel nut, inverted flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external tube 1st end

Features Provided:

Reusable end fittings

Burst Test Pressure:

2000.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire, partial coverage and outer layer rubber impregnated braided fabric

Maximum Operating Pressure:

500.0 pounds per square inch

Thread Size:

0.625 inches 1st end

Seat Angle:

45.0 degrees 1st end

Hydrostatic Test Pressure:

1000.0 pounds per square inch

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

47.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0