NSN 4720-00-559-1603

Nonmetallic Hose Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4720-00-559-1603 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 156.0 degrees fahrenheit single response **Outside Diameter:** 0.500 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 1250.0 pounds per square inch **Layer Composition And Location:** 1st layer braided cotton cord and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 200.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 400.0 pounds per square inch **Outer Covering Environmental Protection:** Abrasion resistant and fuel resistant and oil resistant Vacuum In Torr: 254.0 **Inside Surface Condition:** Smooth **Measuring Method And Length:** 14.000 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response

Unjf 1st end

Thread Series Designator:

NSN 4720-00-559-1603

Nonmetallic Hose Assembly - Page 2 of 2



| Sı | pe | cifi | cati | on | Data: |
|----|--------|------|------|-----|-------|
| • | \sim | ••• | outi | ••• | Dutu. |

88044-an6270 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0