NSN 4720-00-562-0014

Cross Sectional Shape:

Between 0.469 inches and 0.531 inches

Round

Thread Class: 2a 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-562-0014

Tempurature Rating:						
-67.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response						
Outside Diameter:						
Between 0.687 inches and 0.750 inches						
Connection Style:						
Swivel nut with compression sleeve 1st end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Threaded internal tube 1st end						
Thready Qty Per Inch (tpi):						
16 1st end						
Burst Test Pressure:						
750.0 pounds per square inch						
Layer Composition And Location:						
Outer layer braided cotton cord						
Maximum Operating Pressure:						
200.0 pounds per square inch						
Thread Size:						
0.750 inches 1st end						
Seat Angle:						
45.0 degrees 1st end						
Hydrostatic Test Pressure:						
375.0 pounds per square inch						
Outer Covering Environmental Protection:						
Fuel resistant and oil resistant and weatherproof						
Inside Surface Condition:						
Smooth						
Measuring Method And Length:						
20.000 inches						
Media For Which Designed:						
Fuel/oil, hydrocarbon single response						
Thread Series Designator:						
Unf 1st end						

NSN 4720-00-562-0014

Nonmetallic Hose Assembly - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0