

View Online at <https://aerobasegroup.com/nsn/4720-00-571-3492>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.500 inches

**Minimum Inside Bending Radius:**

2.500 inches

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

1600.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided fabric and outer layer molded rubber, chloroprene

**Maximum Operating Pressure:**

400.0 pounds per square inch

**Thread Size:**

0.875 inches 2nd end

**Seat Angle:**

90.0 degrees 2nd end

**Hydrostatic Test Pressure:**

800.0 pounds per square inch

**Outer Covering Environmental Protection:**

Fuel resistant and oil resistant and grease resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

18.000 inches

**Thread Series Designator:**

Unf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0