

View Online at <https://aerobasegroup.com/nsn/4720-00-571-3492>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.500 inches

Minimum Inside Bending Radius:

2.500 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

1600.0 pounds per square inch

Layer Composition And Location:

1st layer braided fabric and outer layer molded rubber, chloroprene

Maximum Operating Pressure:

400.0 pounds per square inch

Thread Size:

0.875 inches 2nd end

Seat Angle:

90.0 degrees 2nd end

Hydrostatic Test Pressure:

800.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and oil resistant and grease resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

18.000 inches

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0