

View Online at <https://aerobasegroup.com/nsn/4720-00-574-6039>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.620 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Flange Thickness:

0.310 inches 2nd end

Outside Diameter:

1.080 inches

Minimum Inside Bending Radius:

6.500 inches

Bolt Hole Quantity:

3 1st end

Connection Style:

Swivel nut flare 1st end

Bolt Hole Diameter:

0.291 inches 2nd end

Raised Face Height:

0.020 inches 2nd end

Raised Face Diameter:

1.250 inches 2nd end

End Flange Construction:

Split 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Layer Composition And Location:

1st layer braided cotton cord and 2nd layer braided steel wire and outer layer braided cotton cord

Maximum Operating Pressure:

1250.0 pounds per square inch

Thread Size:

1.062 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

1500.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Fire resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

26.700 inches working

Flange Style:

Triangular 2nd end

Special Features:

Hose covered w/fire sleeve

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0