Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-574-7902

| Cro | ss Sectional Shape: |
|------|---|
| Rou | Ind |
| Thr | ead Class: |
| 3b 1 | Ist end |
| Thr | ead Direction: |
| Rigi | ht-hand 1st end |
| Insi | de Diameter: |
| 0.62 | 25 inches |
| Ten | npurature Rating: |
| -65. | 0 degrees fahrenheit and 250.0 degrees fahrenheit single response |
| Out | side Diameter: |
| 1.07 | 78 inches |
| Min | imum Inside Bending Radius: |
| 6.50 | 00 inches |
| Ext | erior Color: |
| Gre | en |
| Cor | nnection Style: |
| Swi | vel nut flare 1st end |
| End | I Connection Design: |
| Stra | light 1st end |
| Cor | nnection Type: |
| Thre | eaded internal tube 1st end |
| Fea | tures Provided: |
| Reu | Isable end fittings |
| Thr | eady Qty Per Inch (tpi): |
| 12 1 | lst end |
| Bur | st Test Pressure: |
| 600 | 0.0 pounds per square inch |
| Lay | er Composition And Location: |
| 1st | layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord |
| Max | kimum Operating Pressure: |
| 150 | 0.0 pounds per square inch |
| Thr | ead Size: |
| 1.06 | 62 inches 1st end |
| Sea | t Angle: |
| 37.0 |) degrees 1st end |
| Hyd | Irostatic Test Pressure: |
| 300 | 0.0 pounds per square inch |
| Out | er Covering Environmental Protection: |
| Fue | I resistant and oil resistant |
| Insi | de Surface Condition: |
| Smo | poth |

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 180.000 inches working **Special Features:** Furnished w/two adapters part no. 13217e3961 Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Un 1st end Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0