Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-574-8351

Cross Sectional Shape:
Round
Inside Diameter:
1.000 inches
Flange Thickness:
0.875 inches 2nd end
Outside Diameter:
1.750 inches
Exterior Color:
Black
Angle Between Rigid Elbow Fittings In Deg:
0.0
Center To Center Distance Between Bolt Holes Along Width:
0.719 inches 2nd end
Center To Center Distance Between Bolt Holes Along Length:
2.062 inches 2nd end
Bolt Hole Quantity:
4 2nd end
Flange Length:
2.750 inches 2nd end
Flange Width:
1.218 inches 2nd end
Connection Style:
Plain swivel 2nd end
Bolt Hole Diameter:
0.344 inches 2nd end
End Flange Construction:
Split 2nd end
End Connection Design:
Elbow 2nd end
Connection Type:
Plain face flange 2nd end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
1st layer rubber impregnated braided steel wire and 5th layer molded rubber, synthetic
Maximum Operating Pressure:
5300.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:

126.000 inches working

Flange Style:

Double oval (sae split type flange) 1st end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0