## NSN 4720-00-578-6235

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-578-6235 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 275.0 degrees fahrenheit single response **Outside Diameter:** 0.580 inches **Minimum Inside Bending Radius:** 0.750 inches **Exterior Color:** Green **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Electrostatic discharge capability **Burst Test Pressure:** 800.0 pounds per square inch **Layer Composition And Location:** 1st layer spirally wrapped polytetrafluoroethylene impregnated glass fiber and outer layer spirally wrapped polyamide fabric **Maximum Operating Pressure:** 200.0 pounds per square inch **Thread Size:** 

0.562 inches 1st end

Seat Angle:

37.0 degrees 1st end

**Hydrostatic Test Pressure:** 

400.0 pounds per square inch

**Inside Surface Condition:** 

Convoluted

**Measuring Method And Length:** 

8.000 inches working

**Thread Series Designator:** 

Unjf 1st end

## NSN 4720-00-578-6235

Nonmetallic Hose Assembly - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0