NSN 4720-00-580-2391

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-580-2391

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.344 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.766 inches
Minimum Inside Bending Radius:
5.000 inches
Exterior Color:
Green
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer molded rubber, chloroprene and outer layer braided steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
7000.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and mildew resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:

13.500 inches working

NSN 4720-00-580-2391

Nonmetallic Hose Assembly - Page 2 of 2



Media	For	Which	Design	ed

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

Specification Data:

96906-ms28759 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0