
Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-580-2711

Cross Section	al Shape:
Round	
Thread Class:	
3b 1st end	
Thread Directi	on:
Right-hand 1st	end
Inside Diamete	ər:
0.406 inches	
Tempurature F	Rating:
-40.0 degrees f	ahrenheit single response and 250.0 degrees fahrenheit single response
Outside Diame	eter:
0.734 inches	
Minimum Insid	de Bending Radius:
4.500 inches	
Connection St	yle:
Swivel nut flare	1st end
End Connection	on Design:
Straight 1st end	t
Connection Ty	/pe:
Threaded interr	nal tube 1st end
Thready Qty P	er Inch (tpi):
16 1st end	
Burst Test Pre	essure:
8000.0 pounds	per square inch
Layer Compos	sition And Location:
Outer layer rub	ber impregnated braided cotton cord
Maximum Ope	erating Pressure:
2000.0 pounds	per square inch
Thread Size:	
0.750 inches 1	st end
Seat Angle:	
12.0 degrees 1	st end
Inside Surface	Condition:
Smooth	
Measuring Me	thod And Length:
28.200 inches	working
Thread Series	Designator:
Unf 1st end	
Shelf Life:	
N/a	
Unit Of Measu	re:

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

