Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-580-8667

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.438 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 160.0 degrees fahrenheit single response Outside Diameter:
0.859 inches
Minimum Inside Bending Radius:
5.750 inches
Connection Style: Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
-
37.0 degrees 1st end
Outer Covering Environmental Protection: Abrasion resistant and mildew resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
17.000 inches working
Media For Which Designed:
Air and fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 1st end
Specification Data:
96906-ms28759 government standard

## NSN 4720-00-580-8667

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

