

| Nonmetallic Hose Assembly - Page 1 of 2  |  |
|--|--|
| View Online at https://aerobasegroup.com/nsn/4720-00-580-8672  |  |
| Cross Sectional Shape:   |  |
| Round  |  |
| Thread Class:  |  |
| 3b 1st end   |  |
| Thread Direction:  |  |
| Right-hand 1st end   |  |
| Inside Diameter:   |  |
| 0.438 inches   |  |
| Outside Diameter:  |  |
| 0.859 inches   |  |
| Connection Style:  |  |
| Swivel nut flare 1st end   |  |
| End Connection Design:   |  |
| Straight 1st end   |  |
| Connection Type:   |  |
| Threaded internal tube 1st end   |  |
| Burst Test Pressure:   |  |
| 14000.0 pounds per square inch   |  |
| Layer Composition And Location:  |  |
| 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene |  |
| Maximum Operating Pressure:  |  |
| 3000.0 pounds per square inch  |  |
| Thread Size:   |  |
| 0.750 inches 1st end   |  |
| Seat Angle:  |  |
| 37.0 degrees 1st end   |  |
| Outer Covering Environmental Protection:   |  |
| Abrasion resistant and mildew resistant  |  |
| Inside Surface Condition:  |  |
| Smooth   |  |
| Measuring Method And Length:   |  |
| 300.000 inches working   |  |
| Media For Which Designed:  |  |
| Air and fuel/oil, hydrocarbon single response  |  |
| Thread Series Designator:  |  |
| Unf 1st end  |  |
| Shelf Life:  |  |
| N/a  |  |
| Unit Of Measure:   |  |
|  |  |
| Demilitarization:  |  |
| No   |  |
|  |  |

## NSN 4720-00-580-8672

Nonmetallic Hose Assembly - Page 2 of 2

**Fiig:** A542a0

